

15W/m · IP67 · 24V · CRI>90

			Code	CCT (K)	Lumen output	Cut	LED/m
Power 15 W/m	Life Time 75.000 h	PCB Thickness 3 oz	84174	 RGB	225 Lm/M	62.5 mm	96 LED/m
			84175	 RGB + W 3000K	400 Lm/M	71.4 mm	196 LED/m
			84176	 RGB + W 4000K	420 Lm/M	71.4 mm	196 LED/m
			84177	 Red	125 Lm/M	50 mm	140 LED/m
			84178	 Blue	95 Lm/M	50 mm	140 LED/m
Voltage 24V	CRI >90	SDMC ≤3	84179	 Green	435 Lm/M	50 mm	140 LED/m
			84180	 Yellow	400 Lm/M	50 mm	140 LED/m
			84181	 Pink	235 Lm/M	50 mm	140 LED/m

LED SMD
2835

Silicone

30 m

120°

IP
67

Non
Flicker

30 m

12 mm

Max length 10m

20 mm

20 mm

24 mm

26.5 mm

300 mm

Dimension

20mm

12mm

Minimum Diam
300mm

Light Beam

LIGHT SURFACE

Horizontal Bending

Importante instalar disipador de calor / Important to install heat sink / Important d'installer le dissipateur de chaleur / Importante installare il dissipatore di calore




ACCESSORIES


Code	Description
84163	Perfil recto 1 m / Straight profile 1 m / Profilé droit 1 m
84164	Clip de sujeción / Support clip / Clip support
84165	Tapa final / End cap / Embout de fermeture finale
84166	Tapa inicial / Initial cover / Embout de fermeture initiale
84167	Tapa inicial lateral / Side initial cover / Embout de fermeture initiale latérale




JACKSON




84163




84164



84165



84166



84167