

ALASKA

RGB

14.4W/m · IP65 · 24V · CRI>80

Power	Life Time	PCB Thickness	Code	CCT (K)	Lumen output	M
14.4 W/m	75.000 h	3 oz	84471	RGB	540 Lm/M	1 m/L
Voltage	CRI	SDMC	84473	RGB	540 Lm/M	5 m Roll
24V	>80	≤3				

LED SMD
5050 RGB

5 - 30 m

60 LED/m

IP
65

RGB

100 mm

120°

Non
Flicker

Diagram showing LED strip dimensions: 100 mm, 5 m/30 m, PITCH 16.7 mm, 10 mm, 4 mm, Max length 10 m.

Importante instalar disipador de calor / Important to install heat sink / Important d'installer le dissipateur de chaleur / Importante installare il dissipatore di calore



RIAD

DOHA

LEON

VILNA

MUNICH

MONACO

NAPLES

NAGOYA

BAKU

BUSAN

MUMBAI

QUEBEC

ARGEL

NILO

GANGES

TURIA

TAJO

XINGU

CANTON

VICTORIA

LYON

TURIN

RIGA

ESSEN

LAGOS

GLASGOW

ROMA

LEEDS

UTENA

MONTREAL

RECIFE

EBRO

BURDEOS

HANOI

KAUNAS

KUWAIT

YEDA

TALLIN

DAKAR

BASILEA

MONTERREY

HARBIN

ZURICH

ULSAN

LINZ

PERTH

DELHI

VOLGA

BRAVO

ANKARA

LIEJA

VALENCIA

LUGO

HEFEI

SURAT

CALCUTA

BERNA

BURSA

BARI

CALGARY

BONN

VARNA

MURCIA

COLONIA

SENA

BREMEN

MACAU

TIGRIS

SEVILLA

OSLO

NANTES

NIZA

HAIFA

BANGKOK

ATLANTA

Compatible / Compatibile

No compatible / Not compatible / Non compatible / Non compatibile

*m/L: Lineal meter