

NEVADA

6W/m · IP67 · 24V · CRI>80

Power	Life Time	PCB Thickness	Code	CCT (K)	Lumen output	Lm/W
6 W/m	75.000 h	3 oz	86028	2700K	780 Lm/M	130 Lm/W
			80029	3000K	800 Lm/M	133 Lm/W
Voltage	CRI	SDMC	80030	4000K	820 Lm/M	136 Lm/W
24V	>80	≤3	80031	6000K	840 Lm/M	140 Lm/W

LED SMD
2835

20 m

56 LED/m

IP
67

Silicone

125 mm

120°

Non
Flicker

20 m
125 mm
PITCH 17.9 mm
10 mm
4.4 mm
Max length 10 m

Importante instalar disipador de calor / Important to install heat sink / Important d'installer le dissipateur de chaleur / Importante installare il dissipatore di calore

3YEAR
GUARANTEE

TEST
LM 80

-20 / +50

Dimmable

RoHS

CE

UL

ETL

RIAD

DOHA

LEON

VILNA

MUNICH

MONACO

NAPOLES

NAGOYA

BAKU

BUSAN

MUMBAI

QUEBEC

ARGEL

NILO

GANGES

TURIA

TAJO

XINGU

CANTON

VICTORIA

LYON

TURIN

RIGA

ESSEN

LAGOS

GLASGOW

ROMA

LEEDS

UTENA

MONTREAL

RECIFE

EBRO

BURDEOS

HANOI

KAUNAS

KUWAIT

YEDA

TALLIN

DAKAR

BASILEA

MONTERREY

HARBIN

ZURICH

ULSAN

LINZ

PERTH

DELHI

VOLGA

BRAVO

ANKARA

LIEJA

VALENCIA

LUGO

HEFEI

SURAT

CALCUTA

BERNA

BURSA

BARI

CALGARY

BONN

VARNNA

MURCIA

COLONIA

SENA

BREMEN

MACAU

TIGRIS

SEVILLA

OSLO

NANTES

NIZA

HAIFA

BANGKOK

ATLANTA

Compatible / Compatibile

No compatible / Not compatible / Non compatible / Non compatibile