

SANTORINI

4.8W/m · IP20 · 24V · CRI>80

Power	Life Time	PCB Thickness	Code	CCT (K)	Lumen output	Lm/W
4.8 W/m	75.000 h	3 oz	83991	2700K	432 Lm/M	90 Lm/W
			83992	3000K	437 Lm/M	91 Lm/W
Voltage	CRI	SDMC	83993	4000K	447 Lm/M	93 Lm/W
24V	>80	≤3	83994	6000K	456 Lm/M	95 Lm/W

LED SMD
2835

30 m

120 LED/m

IP
20

Test
LM 80

50 mm

120°

Non
Flicker

Importante instalar disipador de calor / Important to install heat sink / Important d'installer le dissipateur de chaleur / Importante installare il dissipatore di calore



RIAD

DOHA

LEON

VILNA

MUNICH

MONACO

NAPOLIS

NAGOYA

BAKU

BUSAN

MUMBAI

QUEBEC

ARGEL

NILO

GANGES

TURIA

TAJO

XINGU

CANTON

VICTORIA

LYON

TURIN

RIGA

ESSEN

LAGOS

GLASGOW

ROMA

LEEDS

UTENA

MONTREAL

RECIFE

EBRO

BURDEOS

HANOI

KAUNAS

KUWAIT

YEDA

TALLIN

DAKAR

BASILEA

MONTERREY

HARBIN

ZURICH

ULSAN

LINZ

PERTH

DELHI

VOLGA

BRAVO

ANKARA

LIEJA

VALENCIA

LUGO

HEFEI

SURAT

CALCUTA

BERNA

BURSA

BARI

CALGARY

BONN

VARNA

MURCIA

COLONIA

SENA

BREMEN

MACAU

TIGRIS

SEVILLA

OSLO

NANTES

NIZA

HAIFA

BANGKOK

ATLANTA

Compatible / Compatible

No compatible / Not compatible / Non compatible / Non compatibile