

SANTORINI

4.8W/m · IP67 · 24V · CRI>80

|         |           |               |       |         |              |         |
|---------|-----------|---------------|-------|---------|--------------|---------|
| Power   | Life Time | PCB Thickness | Code  | CCT (K) | Lumen output | Lm/W    |
| 4.8 W/m | 75.000 h  | 3 oz          | 83996 | 2700K   | 432 Lm/M     | 90 Lm/W |
|         |           |               | 83997 | 3000K   | 437 Lm/M     | 91 Lm/W |
| Voltage | CRI       | SDMC          | 83998 | 4000K   | 447 Lm/M     | 93 Lm/W |
| 24V     | >80       | ≤3            | 83999 | 6000K   | 456 Lm/M     | 95 Lm/W |

LED SMD  
2835

Silicone

20 m

50 mm

120 LED/m

120°

IP  
67

Non  
Flicker

Importante instalar disipador de calor / Important to install heat sink / Important d'installer le dissipateur de chaleur / Importante installare il dissipatore di calore

3YEAR  
GUARANTEE

TEST  
LM 80

-20 / +50

Dimmable

CE

UL

RoHS

RIAD

BUSAN

CANTON

LEEDS

YEDA

PERTH

SURAT

COLONIA

HAIFA

DOHA

MUMBAI

VICTORIA

UTENA

TALLIN

DELHI

CALCUTA

SENA

BANGKOK

LEON

QUEBEC

LYON

MONTREAL

DAKAR

VOLGA

BERNA

BREMEN

ATLANTA

VILNA

ARGEL

TURIN

RECIFE

BASILEA

BRAVO

BURSA

MACAU

MUNICH

NILO

RIGA

EBRO

MONTERREY

ANKARA

BARI

TIGRIS

MONACO

GANGES

ESSEN

BURDEOS

HARBIN

LIEJA

CALGARY

SEVILLA

NAPLES

TURIA

LAGOS

HANOI

ZURICH

VALENCIA

BONN

OSLO

NAGOYA

TAJO

GLASGOW

KAUNAS

ULSAN

LUGO

VARNA

NANTES

BAKU

XINGU

ROMA

KUWAIT

LINZ

HEFEI

MURCIA

NIZA

Compatible / Compatible

No compatible / Not compatible / Non compatible / Non compatibile