

MIAMI

9.6W/m · IP20 · 24V · CRI>80

			Code	CCT (K)	Lumen output	Lm/W
Power	Life Time	PCB Thickness	86000	2200K	1240 Lm/M	129 Lm/W
9.6 W/m	75.000 h	3 oz	84000	2700K	1258 Lm/M	131 Lm/W
			84001	3000K	1277 Lm/M	133 Lm/W
Voltage	CRI	SDMC	84002	4000K	1296 Lm/M	135 Lm/W
24V	>80	≤3	84003	6000K	1344 Lm/M	140 Lm/W

LED SMD
2835

30 m

140 LED/m

IP
20

Test
LM 80

50 mm

120°

Non
Flicker

Importante instalar disipador de calor / Important to install heat sink / Important d'installer le dissipateur de chaleur / Importante installare il dissipatore di calore



RIAD	DOHA	LEON	VILNA	MUNICH	MONACO	NAPLES	NAGOYA	BAKU
BUSAN	MUMBAI	QUEBEC	ARGEL	NILO	GANGES	TURIA	TAJO	XINGU
CANTON	VICTORIA	LYON	TURIN	RIGA	ESSEN	LAGOS	GLASGOW	ROMA
LEEDS	UTENA	MONTREAL	RECIFE	EBRO	BURDEOS	HANOI	KAUNAS	KUWAIT
YEDA	TALLIN	DAKAR	BASILEA	MONTERREY	HARBIN	ZURICH	ULSAN	LINZ
PERTH	DELHI	VOLGA	BRAVO	ANKARA	LIEJA	VALENCIA	LUGO	HEFEI
SURAT	CALCUTA	BERNA	BURSA	BARI	CALGARY	BONN	VARNA	MURCIA
COLONIA	SENA	BREMEN	MACAU	TIGRIS	SEVILLA	OSLO	NANTES	NIZA
HAIFA	BANGKOK	ATLANTA						

Compatible / Compatibile

No compatible / Not compatible / Non compatible / Non compatibile