

CALIFORNIA

12W/m · IP20 · 24V · CRI>90

			Code	CCT (K)	Lumen output	Lm/W
Power	Life Time	PCB Thickness	86079	● 2200K	1000 Lm/M	84 Lm/W
			84080	● 2700K	1050 Lm/M	88 Lm/W
Voltage	CRI	SDMC	84081	● 3000K	1120 Lm/M	93 Lm/W
			84082	○ 4000K	1200 Lm/M	100 Lm/W
			84083	● 6000K	1280 Lm/M	106 Lm/W
12 W/m	75.000 h	3 oz				
24V	>90	≤3				

LED

COB

Test

LM 80

30 m

480 LED/m

IP 20

50 mm

120°

Non

Flicker

Importante instalar disipador de calor / Important to install heat sink / Important d'installer le dissipateur de chaleur / Importante installare il dissipatore di calore



RIAD

DOHA

LEON

VILNA

MUNICH

MONACO

NAPLES

NAGOYA

BAKU

BUSAN

MUMBAI

QUEBEC

ARGEL

NILO

GANGES

TURIA

TAJO

XINGU

CANTON

VICTORIA

LYON

TURIN

RIGA

ESSEN

LAGOS

GLASGOW

ROMA

LEEDS

UTENA

MONTREAL

RECIFE

EBRO

BURDEOS

HANOI

KAUNAS

KUWAIT

YEDA

TALLIN

DAKAR

BASILEA

MONTERREY

HARBIN

ZURICH

ULSAN

LINZ

PERTH

DELHI

VOLGA

BRAVO

ANKARA

LIEJA

VALENCIA

LUGO

HEFEI

SURAT

CALCUTA

BERNA

BURSA

BARI

CALGARY

BONN

VARNA

MURCIA

COLONIA

SENA

BREMEN

MACAU

TIGRIS

SEVILLA

OSLO

NANTES

NIZA

HAIFA

BANGKOK

ATLANTA

Compatible / Compatible

No compatible / Not compatible / Non compatible / Non compatibile