

TAOS

9.6W/m · IP20 · 24V · CRI>80

			Code	CCT (K)	Lumen output	Lm/W	M
Power 9.6 W/m	Life Time 75.000 h	PCB Thickness 3 oz	84350	● 2700K	864 Lm/M	90 Lm/W	1 m/L
			84351	● 3000K	874 Lm/M	91 Lm/W	
			84352	○ 4000K	892 Lm/M	93 Lm/W	
			84353	● 6000K	912 Lm/M	95 Lm/W	
			84355	● 2700K	864 Lm/M	90 Lm/W	
Voltage 24V	CRI >80	SDMC ≤3	84356	● 3000K	874 Lm/M	91 Lm/W	5 m Roll
			84357	○ 4000K	892 Lm/M	93 Lm/W	
			84358	● 6000K	912 Lm/M	95 Lm/W	

LED SMD
2835

5-30 m

60 LED/m

IP
20

Test
LM 80

100 mm

120°

Non
Flicker

Importante instalar disipador de calor / Important to install heat sink / Important d'installer le dissipateur de chaleur / Importante installare il dissipatore di calore

3YEAR
GUARANTEE

-20 / +50

Dimmable

RIAD	DOHA	LEON	VILNA	MUNICH	MONACO	NAPLES	NAGOYA	BAKU
BUSAN	MUMBAI	QUEBEC	ARGEL	NILO	GANGES	TURIA	TAJO	XINGU
CANTON	VICTORIA	LYON	TURIN	RIGA	ESSEN	LAGOS	GLASGOW	ROMA
LEEDS	UTENA	MONTREAL	RECIFE	EBRO	BURDEOS	HANOI	KAUNAS	KUWAIT
YEDA	TALLIN	DAKAR	BASILEA	MONTERREY	HARBIN	ZURICH	ULSAN	LINZ
PERTH	DELHI	VOLGA	BRAVO	ANKARA	LIEJA	VALENCIA	LUGO	HEFEI
SURAT	CALCUTA	BERNA	BURSA	BARI	CALGARY	BONN	VARNA	MURCIA
COLONIA	SENNA	BREMEN	MACAU	TIGRIS	SEVILLA	OSLO	NANTES	NIZA
HAIFA	BANGKOK	ATLANTA						

Compatible / Compatibile

No compatible / Not compatible / Non compatible / Non compatibile

*m/L: Lineal meter