

TAOS

9.6W/m · IP65 · 24V · CRI>80

			Code	CCT (K)	Lumen output	Lm/W	M
Power 9.6 W/m	Life Time 75.000 h	PCB Thickness 3 oz	84360	2700K	864 Lm/M	90 Lm/W	1 m/L
			84361	3000K	874 Lm/M	91 Lm/W	
			84362	4000K	892 Lm/M	93 Lm/W	
			84363	6000K	912 Lm/M	95 Lm/W	
			84365	2700K	864 Lm/M	90 Lm/W	
Voltage 24V	CRI >80	SDMC ≤3	84366	3000K	874 Lm/M	91 Lm/W	5 m Roll
			84367	4000K	892 Lm/M	93 Lm/W	
			84368	6000K	912 Lm/M	95 Lm/W	

LED SMD
2835

5-20 m

120 LED/m

IP
65

Silicone

100 mm

120°

Non
Flicker

Importante instalar disipador de calor / Important to install heat sink / Important d'installer le dissipateur de chaleur / Importante installare il dissipatore di calore

3YEAR
GUARANTEE

TEST
LM 80

RIAD

DOHA

LEON

VILNA

MUNICH

MONACO

NAPLES

NAGOYA

BAKU

BUSAN

MUMBAI

QUEBEC

ARGEL

NILO

GANGES

TURIA

TAJO

XINGU

CANTON

VICTORIA

LYON

TURIN

RIGA

ESSEN

LAGOS

GLASGOW

ROMA

LEEDS

UTENA

MONTREAL

RECIFE

EBRO

BURDEOS

HANOI

KAUNAS

KUWAIT

YEDA

TALLIN

DAKAR

BASILEA

MONTERREY

HARBIN

ZURICH

ULSAN

LINZ

PERTH

DELHI

VOLGA

BRAVO

ANKARA

LIEJA

VALENCIA

LUGO

HEFEI

SURAT

CALCUTA

BERNA

BURSA

BARİ

CALGARY

BONN

VARNA

MURCIA

COLONIA

SENA

BREMEN

MACAU

TIGRIS

SEVILLA

OSLO

NANTES

NIZA

HAIFA

BANGKOK

ATLANTA

Compatible / Compatibile

No compatible / Not compatible / Non compatible / Non compatibile

*m/L: Lineal meter