

TAOS

9.6W/m · IP65 · 24V · CRI>80

			Code	CCT (K)	Lumen output	Lm/W	M
Power 9.6 W/m	Life Time 75.000 h	PCB Thickness 3 oz	84360	2700K	864 Lm/M	90 Lm/W	1 m/L
			84361	3000K	874 Lm/M	91 Lm/W	
			84362	4000K	892 Lm/M	93 Lm/W	
			84363	6000K	912 Lm/M	95 Lm/W	
			84365	2700K	864 Lm/M	90 Lm/W	
Voltage 24V	CRI >80	SDMC ≤3	84366	3000K	874 Lm/M	91 Lm/W	5 m Roll
			84367	4000K	892 Lm/M	93 Lm/W	
			84368	6000K	912 Lm/M	95 Lm/W	

LED SMD
2835

5-20 m

60 LED/m

IP
65

Silicone

100 mm

120°

Non
Flicker

Importante instalar disipador de calor / Important to install heat sink / Important d'installer le dissipateur de chaleur / Importante installare il dissipatore di calore

3YEAR
GUARANTEE

TEST
LM 80

-20 / +50

Dimmable

RoHS

CE

UL

EneC

EneUS

Compatible / Compatibile

No compatible / Not compatible / Non compatible / Non compatibile

*m/L: Lineal meter