

MISURI

14.4W/m · IP20 · 24V · CRI>80

			Code	CCT (K)	Lumen output	Lm/W	M
Power 14.4 W/m	Life Time 75.000 h	PCB Thickness 3 oz	84410	2700K	1325 Lm/M	92 Lm/W	1 m/L
			84411	3000K	1354 Lm/M	94 Lm/W	
			84412	4000K	1397 Lm/M	97 Lm/W	
			84413	6000K	1440 Lm/M	100 Lm/W	
			84415	2700K	1325 Lm/M	92 Lm/W	
Voltage 24V	CRI >80	SDMC ≤3	84416	3000K	1354 Lm/M	94 Lm/W	5 m Roll
			84417	4000K	1397 Lm/M	97 Lm/W	
			84418	6000K	1440 Lm/M	100 Lm/W	

LED SMD
2835

5-30 m

70 LED/m

IP
20

Test
LM 80

100 mm

120°

Non
Flicker

Importante instalar disipador de calor / Important to install heat sink / Important d'installer le dissipateur de chaleur / Importante installare il dissipatore di calore



RIAD

DOHA

LEON

VILNA

MUNICH

MONACO

NAPLES

NAGOYA

BAKU

BUSAN

MUMBAI

QUEBEC

ARGEL

NILO

GANGES

TURIA

TAJO

XINGU

CANTON

VICTORIA

LYON

TURIN

RIGA

ESSEN

LAGOS

GLASGOW

ROMA

LEEDS

UTENA

MONTREAL

RECIFE

EBRO

BURDEOS

HANOI

KAUNAS

KUWAIT

YEDA

TALLIN

DAKAR

BASILEA

MONTERREY

HARBIN

ZURICH

ULSAN

LINZ

PERTH

DELHI

VOLGA

BRAVO

ANKARA

LIEJA

VALENCIA

LUGO

HEFEI

SURAT

CALCUTA

BERNA

BURSA

BARI

CALGARY

BONN

VARNA

MURCIA

COLONIA

SENA

BREMEN

MACAU

TIGRIS

SEVILLA

OSLO

NANTES

NIZA

HAIFA

BANGKOK

ATLANTA

Compatible / Compatible

No compatible / Not compatible / Non compatible / Non compatibile

*m/L: Lineal meter