

MISURI

14.4W/m · IP65 · 24V · CRI>80

			Code	CCT (K)	Lumen output	Lm/W	M
Power 14.4 W/m	Life Time 75.000 h	PCB Thickness 3 oz	84420	2700K	1325 Lm/M	92 Lm/W	1 m/L
			84421	3000K	1354 Lm/M	94 Lm/W	
			84422	4000K	1397 Lm/M	97 Lm/W	
			84423	6000K	1440 Lm/M	100 Lm/W	
			84425	2700K	1325 Lm/M	92 Lm/W	
Voltage 24V	CRI >80	SDMC ≤3	84426	3000K	1354 Lm/M	94 Lm/W	5 m Roll
			84427	4000K	1397 Lm/M	97 Lm/W	
			84428	6000K	1440 Lm/M	100 Lm/W	

LED SMD
2835

5-20 m

70 LED/m

IP
65

Silicone

100 mm

120°

Non
Flicker

5 m / 20 m
100 mm
PITCH 14.28 mm
9 mm
4.4 mm
Max length 10 m

Importante instalar disipador de calor / Important to install heat sink / Important d'installer le dissipateur de chaleur / Importante installare il dissipatore di calore

3YEAR
GUARANTEE

TEST
LM 80

-20 / +50

Dimmable

RoHS

CE

UL

EneC

RoHS

Compatible / Compatible

No compatible / Not compatible / Non compatible / Non compatibile

*m/L: Lineal meter